FORK LIFT FTF 28-12



			/ \
1	Lifting capacities		
1.1	Lift capacities at load center C	kg	28000
1.2	Load center "C"	mm	1225
1.3	Lift height with simplex mast	mm	4000
1.4	Lifting speed (unloaded/at rated load)	m/s	0,34/0,32
1.5	Lowering speed (unloaded/at rated load)	m/s	0,25/0,26
1.6	Mast Tilt Forward/Backward	0	6/12
2	Driving speed		,
2.1	Drive speed forward (unloaded/at rated load)	km/h	25/24
2.2	Drive speed reverse (unloaded/ at rated load)	km/h	25/24
2.3	Max incline (unloaded/ at rated load)	%	30/28
2.4	Towbar pull max	kN	160
3	Weight		
3.1	Service weight	kg	38500
3.2	Axle pressure front (unloaded / at rated load)	kg	19000/56700
3.3	Axle pressure rear (unloaded / at rated load)	kg	19500/9800
3.4	Stability factor		1,38
4	Engine		1,55
	•		Volvo/TAD 990 VE
4.1 4.2	Engine make / model name Emission approval EU/US		Volvo/TAD 880 VE
4.3	Fuel		Stage 5 Diesel
4.4	Max Power at rpm	kW / rpm	160kW at 2000rpm
4.5	Max Torque at rpm	Nm / rpm	1075Nm at 1400rpm
4.6	N° cylinders / Displacement	N/cc	6/7700
4.7	Specific fuel consumption	I/h	14 - 20
4.8	Alternator type/power/capacity	/W/Amp	AC/3080/110
4.9	Battery (N°, Voltage, Capacity)	/V/Ah	4, 12V, 88A
5	Transmission	7 7 7 111	1, 121, 001
5 .1			ZF 3WG211
5.2	Brand / model		Hydrodinamic
5.3	Type N° of gears Fw/ Rw		
			3/3
6	Drive Axle		W 1 204
6.1	Make /model		Kessler D91
6.2	Type/ width	mm	Rigido/3200
7	Steering Axle		
7.1	Make /model		OMCI/ASF243
7.2	Steering system		Double acting single cylinder
8	Brake System		
8.1	Machine brakes		Wet disc brakes-hydraulic operated
8.2	Parking brakes		Dry disc
9	Wheels		
9.1	Number of Wheels (front + rear) and type		4+2 Pneumatic
9.2	Tire pressure (front + rear)	Bar	10
9.3	Tire dimensions and ply rating (front + rear)		14.00-24 (PR32)
9.4	Rim dimensions (front + rear)		10.00-24
10	Hydraulic System		
10.1	Pumps (number/ type/ Brand)		One triple gear pumps Parker
10.2	Hydraulic oil cooling system		High efficiency radiator with electric fan
10.3	Max working pressure	Bar	230
11	Cabin		
11.1	Туре		Closed cabin with air conditioning
11.2	Internal Noise Level EN12053	db	72
12	Tanks capacity		
12.1	Hydraulic oil	ı	420
12.2	Fuel diesel	i	380
12.3	Ad-Blue	1	25
13	Forks		
13.1	Туре		"Terminal west"
13.2	Sizes (Lenght x width x thickness)	mm	2450x270x110
13.3	Fork translation and positioner	mm	+/- 450
	STEINBERG GmbH Alexander-Scharff-Str.58	8 41169 Moenchengladha	

STEINBERG GmbH Alexander-Scharff-Str.58 41169 Moenchengladbach Germany Tel.: +49 2161 639 89 17 Fax: +49 2161 917 49 22 Mail: info@steinberg.gmbh Web:www.steinberg.gmbh

