FORK LIFT FTF 15-12



	1.16.1		/ \
1	Lifting capacities		
1.1	Lift capacities at load center C	kg	15000
L.2	Load center "C"	mm	1225
1.3	Lift height with simplex mast	mm	4000
1.4	Lifting speed (unloaded/at rated load)	m/s	0,36/0,33
1.5	Lowering speed (unloaded/at rated load)	m/s	0,25/0,26
1.6	Mast Tilt Forward/Backward	0	6/12
2	Driving speed		
2.1	Drive speed forward (unloaded/at rated load)	km/h	25/24
2.2	Drive speed reverse (unloaded/ at rated load)	km/h	25/24
2.3	Max incline (unloaded/ at rated load)	%	26/24
2.4	Towbar pull max	kN	150
3	Weight		
3.1	Service weight	kg	25100
3.2	Axle pressure front (unloaded / at rated load)	kg	11700/36200
3.3	Axle pressure rear (unloaded / at rated load)	kg	13400/3900
3.4	Stability factor		1,4
4	Engine		
4.1	Engine make / model name		Volvo/TAD 582 VE
4.2	Emission approval EU/US		Stage 5
4.3	Fuel		Diesel
4.4	Max Power at rpm	kW / rpm	160kW at 2000rpm
4.5	Max Torque at rpm	Nm / rpm	925Nm at 1380rpm
4.6	N° cylinders / Displacement	N/cc	4/5130
4.7	Specific fuel consumption	l/h	10 - 15
4.8	Alternator type/power/capacity	/W/Amp	AC/3080/110
4.9	Battery (N°, Voltage, Capacity)	/V/Ah	2, 12V, 88A
5	Transmission		
5.1	Brand / model		ZF 3WG171
5.2	Туре		Hydrodinamic
5.3	N° of gears Fw/ Rw		3/3
6	Drive Axle		
6.1	Make /model		Kessler D81
6.2	Type/ width	mm	Rigid/2500
7	Steering Axle		
7.1	Make /model		OMCI/ASF253
7.2	Steering system		Double acting single cylinder
8	Brake System		
8.1	Machine brakes		Wet disc brakes-hydraulic operated
8.2	Parking brakes		Dry disc
	Wheels		Diy disc
9	Number of Wheels (front + rear) and type		4.2 Drawnatia
9.1 9.2	Tire pressure (front + rear)	Bar	4+2 Pneumatic 10
9.3	Tire dimensions and ply rating (front + rear)	Ddl	12.00-20 (PR24)
9.4	Rim dimensions (front + rear)		8,5-00-20
			8,3-00-20
10	Hydraulic System		0
10.1	Pumps (number/ type/ Brand)		One triple gear pump Parker
10.2	Hydraulic oil cooling system		High efficiency radiator with electric fan
10.3	Max working pressure	Bar	200
11	Cabin		
11.1	Туре		Closed cabin with air conditioning
11.2	Internal Noise Level EN12053	db	72
12	Tanks capacity		
12.1	Hydraulic oil	I	350
12.2	Fuel diesel	I	250
12.3	Ad-Blue	I	25
13	Forks		
13.1	Туре		"Terminal west"
13.2	Sizes (Lenght x width x thickness)	mm	2450x220x100
13.3	Fork translation and positioner	mm	+/- 450
	STEINBERG GmbH Alexander-Scharff-Str.58	3 41169 Moenchengladbach	

STEINBERG GmbH Alexander-Scharff-Str.58 41169 Moenchengladbach Germany Tel.: +49 2161 639 89 17 Fax: +49 2161 917 49 22 Mail: info@steinberg.gmbh Web:www.steinberg.gmbh





