

# EMPTY CONTAINER LIFT TRUCK FT 20-H6



<b>1 Lifting data</b>			
1.1	Lift capacities at load center C	kg	8000
1.2	Load center "C"	mm	1225
1.3	Stacking height (9' 6"/8' 6" containers)		5/6
1.4	Lifting speed (unloaded/at rated load)	m/s	0,57/0,55
1.5	Lowering speed (unloaded/at rated load)	m/s	0,52/0,54
1.6	Mast Tilt Forward/Backward	°	3/6
<b>2 Driving speed</b>			
2.1	Drive speed forward (unloaded/at rated load)	km/h	25/25
2.2	Drive speed reverse (unloaded/ at rated load)	km/h	25/25
2.3	Max incline (unloaded/ at rated load)	%	30/25
2.4	Towbar pull max	kN	160
<b>3 Weight</b>			
3.1	Service weight	kg	31500
3.2	Axle pressure front (unloaded / at rated load)	kg	20000/32700
3.3	Axle pressure rear (unloaded / at rated load)	kg	11500/6800
3.4	Stability factor		2,68
<b>4 Engine</b>			
4.1	Engine make / model name		Volvo/ TAD881VE
4.2	Emission approval EU/US		Stage5
4.3	Fuel		Diesel
4.4	Max Power at rpm	kW / rpm	185kW at 2000rpm
4.5	Max Torque at rpm	Nm / rpm	1175Nm at 1400rpm
4.6	N° cylinders / Displacement	N/cc	6/7700
4.7	Specific fuel consumption	l/h	14 to 20
4.8	Alternator type/power/capacity	/W/Amp	AC/3080/110
4.9	Battery (N°, Voltage, Capacity)	/V/Ah	4, 12V, 88A
<b>5 Transmission</b>			
5.1	Brand / model		DANA TE14
5.2	Type		Hydrodynamic
5.3	N° of gears Fw/ Rw		4/4
<b>6 Drive Axle</b>			
6.1	Make /model		Kessler D81
6.2	Type/ width	mm	Rigid/3790
<b>7 Steering Axle</b>			
7.1	Make /model		OMCI/ASF253
7.2	Steering system		Double acting single cylinder
<b>8 Brake System</b>			
8.1	Machine brakes		Wet disc brakes-hydraulic operated
8.2	Parking brakes		Dry disc
<b>9 Wheels</b>			
9.1	Number of Wheels (front + rear) and type		4+2 Pneumatic
9.2	Tire pressure (front + rear)	Bar	10
9.3	Tire dimensions and ply rating (front + rear)		12.00-20 (PR24)
9.4	Rim dimensions (front + rear)		8.5.00-20
<b>10 Hydraulic System</b>			
10.1	Pumps (number/ type/ Brand)		Two triple gear pumps Parker
10.2	Hydraulic oil cooling system		High efficiency radiator with electric fan
10.3	Max working pressure	Bar	160
<b>11 Cabin</b>			
11.1	Type		Closed cabin with air conditioning
11.2	Internal Noise Level EN12053	db	72
<b>12 Tanks capacity</b>			
12.1	Hydraulic oil	l	420
12.2	Fuel diesel	l	360
12.3	Ad-Blue	l	25
<b>13 Lift equipment and spreader</b>			
13.1	Lift mast model / mast type/ Design		Duplex standard/2 stage/free visibility
13.2	Spreader type/make/model		Sidelift telescopic/Mec Service/ SSB100F
13.3	Spreader locking containers/ No of containers		2 x top twist locks / 1
13.4	Sideshift stroke	mm	+600
13.5	Pile slope type/ pile slope stroke	/mm	mechanical/200mm

