

EMPTY CONTAINER LIFT TRUCK FT 25-H8



1	Lifting data		
1.1	Lift capacities at load center C	kg	9000
1.2	Load center "C"	mm	1220
1.3	Stacking height (9' 6"/8' 6" containers)		7/8
1.4	Lifting speed (unloaded/at rated load)	m/s	0,57/0,55
1.5	Lowering speed (unloaded/at rated load)	m/s	0,52/0,54
1.6	Mast Tilt Forward/Backward	°	3/6
2	Driving speed		
2.1	Drive speed forward (unloaded/at rated load)	km/h	25/25
2.2	Drive speed reverse (unloaded/ at rated load)	km/h	25/25
2.3	Max incline (unloaded/ at rated load)	%	30/25
2.4	Towbar pull max	kN	160
3	Weight		
3.1	Service weight	kg	42500
3.2	Axle pressure front (unloaded / at rated load)	kg	28000/41000
3.3	Axle pressure rear (unloaded / at rated load)	kg	14500/10500
3.4	Stability factor		3,1
4	Engine		
4.1	Engine make / model name		Volvo/ TAD881VE
4.2	Emission approval EU/US		Stage5
4.3	Fuel		Diesel
4.4	Max Power at rpm	kW / rpm	185kW a 2000rpm
4.5	Max Torque at rpm	Nm / rpm	1175Nm a 1400rpm
4.6	N° cylinders / Displacement	N/cc	6/7700
4.7	Specific fuel consumption	l/h	14 to 20
4.8	Alternator type/power/capacity	/W/Amp	AC/3080/110
4.9	Battery (N°, Voltage, Capacity)	/V/Ah	4, 12V, 88A
5	Transmission		
5.1	Brand / model		DANA TE14
5.2	Type		Hydrodynamic
5.3	N° of gears Fw/ Rw		4/4
6	Drive Axle		
6.1	Make /model		Kessler D91
6.2	Type/ width	mm	Rigid/4230
7	Steering Axle		
7.1	Make /model		OMCI/ASF243
7.2	Steering system		Double acting single cylinder
8	Brake System		
8.1	Machine brakes		Wet disc brakes-hydraulic operated
8.2	Parking brakes		Dry disc
9	Wheels		
9.1	Number of Wheels (front + rear) and type		4+2 Pneumatic
9.2	Tire pressure (front + rear)	Bar	10
9.3	Tire dimensions and ply rating (front + rear)		14.00-24 (PR24)
9.4	Rim dimensions (front + rear)		10.00-24
10	Hydraulic System		
10.1	Pumps (number/ type/ Brand)		Two triple gear pumps Parker
10.2	Hydraulic oil cooling system		High efficiency radiator with electric fan
10.3	Max working pressure	Bar	185
11	Cabin		
11.1	Type		Closed cabin with air conditioning
11.2	Internal Noise Level EN12053	db	72
12	Tanks capacity		
12.1	Hydraulic oil	l	550
12.2	Fuel diesel	l	400
12.3	Ad-Blue	l	25
13	Lift equipment and spreader		
13.1	Lift mast model / mast type/ Design		Duplex standard/2 stage/free visibility
13.2	Spreader type/make/model		Sidelift telescopic/Mec Service/ SSB100F
13.3	Spreader locking containers/ No of containers		2x top twist locks / 1
13.4	Sideshift stroke	mm	+600
13.5	Pile slope type/ pile slope stroke	/mm	mechanical/200mm

